



## STAINLESS STEEL DISPLAY

RoHS compliant



### ORDERING

LINOX-115P	15"/1024x768/S.S./V/PTC (USB)/9-36V/W ADP
LINOX-115R	15"/1024x768/S.S./V/RT (USB)/9-36V/W ADP
LINOX-115PH	15"/1024x768/1000NITS/S.S./V/PTC (USB)/9-36V/W ADP
LINOX-115RH	15"/1024x768/1000NITS/S.S./V/RT (USB)/9-36V/W ADP

MODEL	LINOX-115	
<b>I/O</b>		
VGA	1x M12 12-pin cable with waterproof cover and chain	
USB	1x M12 USB 2.0 with waterproof cover and chain	
HDMI	1x W.F. HDMI with waterproof cap	
AUDIO	1x 2W IP65 Speaker (Optional)	
OSD	OSD on the rear side	
POWER	1x M12 3-pin for DC power with waterproof cover and chain	
	1x Power Input / 1x Touch ON/OFF button on the side	
<b>DISPLAY</b>		
DISPLAY TYPE	15" TFT-LCD 4:3	
MAX RESOLUTION	1024 x 768	
MAX COLOR	262K / 16.2M	16.7M
BRIGHTNESS (cd/m <sup>2</sup> )	300	1000
VIEW ANGLE (H°/V°)	160/150	176/176
CONTRAST	800:1	2000:1
<b>TOUCHSCREEN</b>		
TYPE	Resistive Zero Bezel (R)   Projected Capacitive (P)	
INTERFACE	USB	
LIGHT TRANSMISSION	Resistive: 80   Capacitive: 90	
<b>POWER</b>		
POWER INPUT	9 ~ 36V DC	
POWER CONSUMPTION	MAX. 9W (P/R) / MAX. 17W (PH/RH)	
<b>MECHANICAL</b>		
CONSTRUCTION	304 Stainless Steel chassis (default)	
	316 Stainless Steel chassis (optional)	
IP RATING	Total IP66 / IP69K	
MOUNTING	VESA Mount 75 x 75 / Yoke mount (Optional)	
DIMENSIONS (mm)	399 x 324 x 53	
NET WEIGHT (kg)	6.5	
<b>ENVIRONMENT</b>		
OPERATING TEMPERATURE	0 ~ 50° C / -20 ~ 60° C (optional)	
STORAGE TEMPERATURE	-30 ~ 70° C	
STORAGE HUMIDITY	10 ~ 95 % @40 non-condensing	
CERTIFICATE	CE/FCC Class A	

