



## STAINLESS STEEL DISPLAY

RoHS compliant



### ORDERING

|             |   |
|-------------|---|
| LINOX-121P  | 21.5"/1920x1080/S.S./V/PTC (USB)/9~36V/W ADP          |
| LINOX-121R  | 21.5"/1920x1080/S.S./V/RT (USB)/9~36V/W ADP           |
| LINOX-121PH | 21.5"/1920x1080/1000NITS/S.S./V/PTC (USB)/9~36V/W ADP |
| LINOX-121RH | 21.5"/1920x1080/1000NITS/S.S./V/RT (USB)/9~36V/W ADP  |

| MODEL                           | LINOX-121   |      |
|---------------------------------|---|------|
| <b>I/O</b>                      |   |      |
| VGA                             | 1x M12 12-pin cable with waterproof cover and chain       |      |
| USB                             | 1x M12 USB 2.0 with waterproof cover and chain            |      |
| HDMI                            | 1x W.F. HDMI with waterproof cap                          |      |
| AUDIO                           | 1x 2W IP65 Speaker (Optional)                             |      |
| OSD                             | OSD on the rear side                                      |      |
| POWER                           | 1x M12 3-pin for DC power with waterproof cover and chain |      |
|                                 | 1x Power Input / 1x Touch ON/OFF button on the side       |      |
| <b>DISPLAY</b>                  |   |      |
| DISPLAY TYPE                    | 21.5" TFT-LCD 16:9  |      |
| MAX RESOLUTION                  | 1920 x 1080   |      |
| MAX COLOR                       | 16.7M   |      |
| BRIGHTNESS (cd/m <sup>2</sup> ) | 250   | 1000 |
| VIEW ANGLE (H°/V°)              | 178/178   |      |
| CONTRAST                        | 3000:1  |      |
| <b>TOUCHSCREEN</b>              |   |      |
| TYPE                            | Resistive Zero Bezel (R)   Projected Capacitive (P)       |      |
| INTERFACE                       | USB   |      |
| LIGHT TRANSMISSION              | Resistive: 80   Capacitive: 90                            |      |
| <b>POWER</b>                    |   |      |
| POWER INPUT                     | 9 ~ 36V DC  |      |
| POWER CONSUMPTION               | MAX. 19W (P/R) / MAX. 25W (PH/RH)                         |      |
| <b>MECHANICAL</b>               |   |      |
| CONSTRUCTION                    | 304 Stainless Steel chassis (default)                     |      |
|                                 | 316 Stainless Steel chassis (optional)                    |      |
| IP RATING                       | Total IP66 / IP69K  |      |
| MOUNTING                        | VESA Mount 100 x 100 / Yoke mount (Optional)              |      |
| DIMENSIONS (mm)                 | 571 x 362 x 55  |      |
| NET WEIGHT (kg)                 | 9.5   |      |
| <b>ENVIRONMENT</b>              |   |      |
| OPERATING TEMPERATURE           | 0 ~ 50° C / -20 ~ 60° C (Optional)                        |      |
| STORAGE TEMPERATURE             | -30 ~ 70° C   |      |
| STORAGE HUMIDITY                | 10 ~ 95% @40 non-condensing                               |      |
| CERTIFICATE                     | CE/FCC Class A  |      |

