



INDUSTRIAL PANEL PC

| MECHANICAL | |
|-----------------|---|
| CONSTRUCTION | Aluminium Front Bezel |
| MOUNTING | Panel Mount, Optional VESA 100x100 |
| DIMENSIONS (mm) | 452 x 356 x 81 |
| NET WEIGHT (kg) | 7.5 Kg |
| IP RATING | IP65 compliant front bezel |
| CERTIFICATE | CE |
| INQUIRY CODES | |
| SLIM-717R-S8 | 17" TFT, 1280x1024, 8/9th Gen. Intel® Core™, RTS, 110~230V AC, 400cd/m2 |
| SLIM-717P-S8 | 17" TFT, 1280x1024, 8/9th Gen. Intel® Core™, PCT, 110~230V AC, 400cd/m2 |
| NOTE | RAM and Storage capacity must be specified in the inquiry |

| MODEL | SLIM-717-S8 | |
|------------------------|---|---------------------------|
| SYSTEM | | |
| CPU | 8/9th Gen. Intel® Core™, i3-8100T i5-8500T i7-8700T, 35W | |
| SYSTEM CHIPSET | Intel® H310 | |
| MEMORY | 2x 260-pin SO-DIMM Dual Channel DDR4, 2666MHz MAX. 64GB (i3 max. 32GB) | |
| OPERATING SYSTEM | Windows 10® | |
| INTERFACE PORTS | | |
| USB | 4x USB 3.1, 4x USB 2.0 | |
| SERIAL | 3x COM RS232, 1x COM RS232/422/485 | |
| LAN | 2x RJ45 GbE LAN (1x Intel® i210, 1x Intel® i219V) with 10/100/1000 Mbps | |
| VIDEO | 2x DP (1.2), 1x VGA, 1x LVDS | |
| AUDIO | 1x Line Out, 1x Mic in, 1x Speaker header | |
| EXPANSIONS | | |
| PCIe | 1x PCIe x16 (Gen3) | |
| Mini-PCIe | 1x Full/Half-size with PCIe x1 and USB 2.0 | |
| STORAGE | | |
| M.2 | 1x M.2 with shared SATA3 for SSD | |
| SATA3 | 4x SATA3 shared with M.2 Key M | |
| DISPLAY | | |
| DISPLAY TYPE | 17" TFT-LCD 4:3 | |
| MAX RESOLUTION | 1280x1024 | |
| MAX COLOR | 16.7M | |
| BRIGHTNESS (cd/m²) | 350 | |
| VIEW ANGLE (H°/V°) | 80/60/80 | |
| CONTRAST | 800:1 | |
| TOUCHSCREEN | | |
| TYPE | Resistive (R) | Projected Capacitive (P) |
| INTERFACE | USB | |
| LIGHT TRANSMISSION | Resistive: 80 | Projected Capacitive: 90% |
| POWER | | |
| POWER INPUT | 110 ~ 230V AC | |
| POWER CONSUMPTION | 45W | |
| ENVIRONMENT | | |
| OPERATING TEMPERATURE | 0 ~ 50° C | |
| STORAGE TEMPERATURE | -20 ~ 70° C | |
| STORAGE HUMIDITY | 10 ~ 90 % non-condensing | |

