



## ALUMINIUM PANEL PC

MECHANICAL	
CONSTRUCTION	Aluminium Front Bezel
MOUNTING	Panel Mount
DIMENSIONS (mm)	410 x 310 x 84
NET WEIGHT (kg)	7
IP RATING	IP66 Front Bezel
CERTIFICATE	CE / FCC Class A
ENVIRONMENT	
OPERATING TEMPERATURE	0 ~ 50° C
STORAGE TEMPERATURE	-20 ~ 70° C
STORAGE HUMIDITY	10 ~ 90% @40 non-condensing
INQUIRY CODES	
SLIM-915R-FN8-V	15" TFT, 1024x768, Intel® Core™ 8th Gen, RST, Alim. 9-36V DC, 410x310x84
SLIM-915P-FN8-V	15" TFT, 1024x768, Intel® Core™ 8th Gen, PCT, Alim. 9-36V DC, 410x310x84
<b>NOTE</b>	RAM and Storage capacity must be specified in the inquiry

MODEL	SLIM-915V-FN8	
<b>SYSTEM</b>		
CPU	8th Gen. Intel® Core™ (Whiskey Lake-U) Processors i3-8145UE, DC, 2.2GHz   i5-8365UE, QC, 1.6GHz	
SYSTEM CHIPSET	MCP	
MEMORY	2x 260-pin SO-DIMM 32GB DDR4 2400MHz	
OPERATING SYSTEM	Windows 10/11®	
GRAPHICS	Intel® Gen9 Graphics DX 12	
<b>INTERFACE PORTS</b>		
USB	6x USB 3.2 (2x Gen1, 4x Gen2), 2x USB 2.0	
SERIAL	3x COM RS232, 1x COM RS232/422/485	
LAN	2x RJ45 Gigabit LAN (1x Intel i219-LM/V, 1x Intel i210) 10/100/1000 Mbps	
VIDEO PORTS	2x DP (1.2), 1x LVDS 4x GPO + 4x GPI	
AUDIO	2x Audio (Mic-In, Line-Out), 1x Speaker header	
OTHERS	2x additional LAN (optional)	
<b>STORAGE</b>		
M.2	1x Key M (2242/2280) with PCIe x4 and SATA3 for SSD	
SATA	1x SATA3	
<b>EXPANSIONS</b>		
M.2	1x Key E (2230) with Mini-PCIe x1, USB 2.0 for Wireless	
<b>DISPLAY</b>		
DISPLAY TYPE	15" TFT-LCD 4:3	
MAX RESOLUTION	1024 x 768	
MAX COLOR	16.7M	
BRIGHTNESS (cd/m²)	500	
VIEW ANGLE (H°/V°)	85/85	
CONTRAST	1500:1	
<b>TOUCHSCREEN</b>		
TYPE	Resistive (R)	Projected Capacitive (P)
INTERFACE	USB	
LIGHT TRANSMISSION	Resistive: 80%	Projected Capacitive: 90%
<b>POWER</b>		
POWER INPUT	9 ~ 36V DC	
POWER CONSUMPTION	50W	
POWER PORTS	1x ON/OFF Power button, 1x 3-pin DC Power	

# SLIM-915V-FN8

