



ALUMINIUM PANEL PC

MECHANICAL	
CONSTRUCTION	Aluminium Front Bezel, Aluminium die-casting chassis
MOUNTING	Panel Mount, VESA 100x100
DIMENSIONS (mm)	412 x 277.5 x 58.9
NET WEIGHT (kg)	4.5 kg
IP RATING	IP66 compliant front bezel
CERTIFICATE	CE / FCC Class A
ENVIRONMENT	
OPERATING TEMPERATURE	0 ~ 50° C -20 ~ 60° C (Optional)
STORAGE TEMPERATURE	-30 ~ 70° C
STORAGE HUMIDITY	10 ~ 95% @40 non-condensing
INQUIRY CODES	
VISION-916AR	15.6" TFT, 1024x768, Intel® Core 6th Gen, RTS, 9-36V DC, 420cd/m2
VISION-916ARH	15.6" TFT, 1024x768, Intel® Core 6th Gen, RTS, 9-36V DC, 1000cd/m2
VISION-916AP	15.6" TFT, 1024x768, Intel® Core 6th Gen, PCT, 9-36V DC, 420cd/m2
VISION-916APH	15.6" TFT, 1024x768, Intel® Core 6th Gen, PCT, 9-36V DC, 1000cd/m2
NOTE	CPU, Resolution, RAM and Storage capacity must be specified in the inquiry

VISION-916A	
SYSTEM	
CPU	Onboard 6th Gen Intel® Core i3-6100U Processor 2.3GHz
	Onboard 6th Gen Intel® Core i5-6300U Processor 2.3GHz
SYSTEM CHIPSET	SoC
MEMORY (MAX)	1x 260-pin SO-DIMM DDR4 up to 16GB 2133MHz
OPERATING SYSTEM	Windows 7/10®
GRAPHICS	Intel HD® Graphics 520
INTERFACE PORTS	
USB/SERIAL	2x USB 3.0 Type A, 1x DB9 COM1 RS232/422/485, 1x DB9 RS232
LAN	2x GbE LAN RJ-45
AUDIO	1x Audio Line Out
ADDITIONAL PORTS TB-528 Module	4G LTE Wi-Fi 4/5/6 + BT 4x USB 2.0 type A
	4x USB 2.0 type A + 1x Mini-PCIe + 1 SIM slot 2x COM
	1x COM + 2x USB 2.0 1x COM + 2x USB 2.0 + 1x Power Button
	2x COM + 1x Mini-PCIe slot + 1x SIM slot 2x Conf. COM 2x CAN
	1x LAN + 2x USB 2.0 type A
UPS (Optional)	1x LAN (45W isolated POE PD) + 2x USB 2.0 type A (TB-528E1U2U POE) VESA Stand UPS Battery 21W - UPS and TB-528 board can not coexist
STORAGE	
HDD	1x 2.5" SATA3 HDD SPACE
EXPANSIONS	
Onboard expansion bus	1x Mini-PCIe slot (full size)
DISPLAY	
DISPLAY TYPE	15.6" TFT-LCD 16:9
MAX RESOLUTION	1366 x 768 1920 x 1080
MAX COLOR	16.2M / 16.7M
BRIGHTNESS (cd/m²)	420/450 1000
VIEW ANGLE (H°/V°)	170/170
CONTRAST	500:1 800:1
TOUCHSCREEN	
TYPE	Resistive (R) Projected Capacitive (P)
INTERFACE	USB
LIGHT TRANSMISSION	Resistive 80% Capacitive 90%
POWER	
POWER INPUT	9 ~ 36V DC
POWER CONSUMPTION	MAX. 52W
POWER PORTS	1x 3-pin Terminal Block Connector 1x 2-pin Power Switch Connector

