



CUSTOMIZABLE PANEL PC

MECHANICAL	
CONSTRUCTION	Aluminium Front Bezel with customizable front
MOUNTING	Panel Mount
DIMENSIONS (mm)	564 x 348 x 83
NET WEIGHT (kg)	8.5 kg
IP RATING	IP65
CERTIFICATE	CE
ENVIRONMENT	
OPERATING TEMPERATURE	0 ~ 50° C
STORAGE TEMPERATURE	-30 ~ 70° C
STORAGE HUMIDITY	10 ~ 90 % non-condensing
INQUIRY CODES	
WPC-921-FN8	21.5", 1920x1080, 8th Gen. Intel® Core, IP65, RST, 9-36V DC, 300 cd/m2
NOTE	RAM and Storage capacity must be specified in the inquiry

MODEL	WPC-921-FN8
SYSTEM	
CPU	8th Gen. Intel® Core™ (Whiskey Lake-U), 15W i3-8145UE, DC, 2.2GHz i5-8365UE, QC, 1.6GHz i7-8665UE, QC, 1.7GHz
SYSTEM CHIPSET	MPC
MEMORY	2x 260-pin SO-DIMM Dual Channel DDR4 2400 MHz, max. 32GB
OPERATING SYSTEM	Windows 10/11®
GRAPHICS	Intel Gen9 Graphics DX 12
INTERFACE PORTS	
LAN	2x GbE RJ45 LAN (1x Intel® i219LM, 1x Intel® i211AT) 10/100/1000 Mbps
SERIAL	3x COM (RS232), 1x COM (RS232/422/485)
USB	6x USB 3.2 (Gen2 + Gen1), 2x USB 2.0
VIDEO	2x DP 1.2, 1x LVDS
GPIO	4x GPI + 4x GPO
AUDIO	2x Audio (Mic-In, Line-Out)
STORAGE	
M.2	1x Key M (2242/2280) with PCIe x4 and SATA3 for SSD 1x Key M (2242) with SATA3 for SSD
SATA	1x SATA3 (6Gb/s)
EXPANSIONS	
M.2	1x Key E (2230) with PCIe x1, CNVI and USB 2.0 for Wireless
DISPLAY	
DISPLAY TYPE	21.5" TFT-LCD 16:9
MAX RESOLUTION	1920 x 1080 (F)
MAX COLOR	16.7M
BRIGHTNESS (cd/m²)	300
VIEW ANGLE (H°/V°)	89/89
CONTRAST	5000:1
TOUCHSCREEN	
TYPE	Resistive (R)
INTERFACE	USB
LIGHT TRANSMISSION	Resistive: 80%
POWER	
POWER INPUT	12 ~ 36V DC
POWER CONSUMPTION	50W
POWER PORTS	1x Power ON/OFF button, 1x 4-pin DC-in jack

